## Carpofit

## Carpet cleaner

Product discription	Carpet extraction cleaner.	
Properties	pH neutral product voor cleaning of all soft floor coverings and upholstery fabrics.	
Usage	Hako Carpofit is a low foam carpet cleaner, suitable for use on any type of carpet or upholstery fabric. Hako Carpofit removes easily fat and waterbased dirt. Suitable for any type of carpet extraction machine and padmethode, also suitable as prespray agent and spotremover.	
Dilution	Spray extraction: 10 - 30 ml per litre water (1 - 3% / 1:100 - 1:35) Padcleaning: 30 - 50 ml per litre water (3 - 5% / 1:35 - 1:20) Prespray/spotremover: 50 - 100 ml per litre water (5 - 10% / 1:20 - 1:10) Depending on the amount of dirt.	
Instructions	Add the right amount product to clean, cold or handwarm water. Spray extraction: fill the clean-water tank with water and add the product, distribute Hako Defoam over the walls of the waste tank of the machine, spray-extract the carpet or upholstery fabrics and suck the cleaned surface afterwards. Padcleaning: fill a spraybot -tle with water and add the product. Spray the surface with the cleaningsolution and remove dirt with a damp bonnet-pad. Prespray/spotremoving: fill a spraybottle with water and add the product, spray the traffic lane or spot with the cleaningsolution. Let the solution soak several minutes and remove dirt with a carpet extraction machine or a white absorbing (terry) towel.	
<b>Technical data</b> pH value undiluted Scent Colour Density	About (7) Characteristic Colourless 1 g/ml	
Order unit	99703500 10 litre jerrycan	

<u>General data:</u>

• Manufactured by Hilco Chemie B.V., a division of the Hako group

• Store frost-free, keep cool and dark. Can be kept / stored in unopened packaging for 12 months.

• Hako does not accept any responsibility / liability caused by incorrect or wrong usage.

• A safety data sheet (SDS) is available upon request for the professional user.

Hako GmbH Hamburger Straße 209-239 D-23843 Bad Oldesloe Tel: (04531) 806 0 Fax: (04531) 806 338



E-Mail: info@hako.com Web: www.hako.com