## Defoam

## Anti-foaming

**Product description** | Anti-foaming agent.

**Properties** Neutral anti-foaming agent based on silicone.

Hako Defoam is designed for use in the waste tank in scrubberdrier

machines and carpet extraction machines.

**Usage** Hako Defoam is suitable for use in the waste tank of scrubber-drier

machines and carpet extraction machines to prevent formation of foam. The vacuummotor of the machine can get damaged when

foam reaches the motor.

Dilution Scrubber-drier machines:

50 - 250 ml per 100 litre waste tankcapacity.

Carpet extraction machines:

Add 100 ml per litre clean, cold water.

Use 50 - 250 ml solution per 10 litre waste tankcapacity.

Instructions Distribute Hako Defoam or the Hako Defoam solution over the

walls of the waste tank of the machine.

Technical data

pH value undiluted About (7)
Scent Characteristic

Colour White
Density 1 g/ml

**Order unit** 99702000 Box of 2 x 5 litre jarrycans











- Manufactured by Hilco Chemie B.V., a division of the Hako group
- Store frost-free, keep cool and dark. Can be kept / stored in unopened packaging for 12 months.
- Hako does not accept any responsibility / liability caused by incorrect or wrong usage.
- A safety data sheet (SDS) is available upon request for the professional user.

Hako GmbH Hamburger Straße 209-239 D-23843 Bad Oldesloe Tel: (04531) 806 0 Fax: (04531) 806 338

E-Mail: info@hako.com Web: www.hako.com

